


Thyristor Surge Suppressors



Features

- Low switching voltage
- Low on-state voltage
- Does not degrade surge capability after multiple surge events within limit
- Fails short circuit when surged in excess of ratings
- Low Capacitance

Typical Applications

- Protect circuit

Mechanical Data

- **Package:** DO-214AA (SMB)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102



■Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	Max
Storage temperature	T _{stg}	°C	-55~+150
Junction temperature	T _j	°C	-55~+150

■Thermal Characteristics (T_a=25°C Unless otherwise specified)

Part Number	V _{drm} @I _{drm} =5μA (V)	V _s @100V/μs (V)	V _t @I _t =2.2Amps (V)	I _{drm} @V _{drm} (μA)	I _s (mA)	I _t (A)	I _h (mA)	C _o @1MHz, 2V bias (pF)
	Min	Max	Max	Max	Max	Max	Min	Typ.
P0080S_	6	25	4	5	800	2.2	30	60
P0300S_	25	40	4	5	800	2.2	50	65
P0640S_	58	77	4	5	800	2.2	120	45
P0720S_	65	88	4	5	800	2.2	120	45
P0900S_	75	98	4	5	800	2.2	120	40
P1100S_	90	130	4	5	800	2.2	120	40
P1300S_	120	160	4	5	800	2.2	120	40
P1500S_	140	180	4	5	800	2.2	120	35
P1800S_	170	220	4	5	800	2.2	120	65
P2300S_	190	260	4	5	800	2.2	120	60
P2600S_	220	300	4	5	800	2.2	120	45



SMBJ TSS SERIES

P3100S_	275	350	4	5	800	2.2	120	45
P3500S_	320	400	4	5	800	2.2	120	40
P4000S_	360	460	4	5	800	2.2	120	40

For individual “SA”, “SB”, and “SC” surge ratings, see table below.

Series	Ipp 10/700us (A)	Ipp 8/20us (A)	Ipp 10/1000us (A)
	Min	Min	Min
A	50	150	45
B	100	250	80
C	150	400	100

■ Characteristics (Typical)

FIG1:V-I Characteristics




FIG2: tr*td Pulse Wave-form




FIG3:Normalized Vs Change versus Junction Temperature





FIG4:Normalized DC Holding Current






SMBJ TSS SERIES

■ Ordering Information (Example)


PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
P0080SA-P4000SC	F1	Approximate 0.0975	3000	/	48000	13" reel

■ Outline Dimensions



DO-214AA(SMB)		
Dim	Min	Max
A	1.85	2.15
B	3.30	3.94
C	4.05	4.75
D	1.99	2.61
E	5.21	5.59
F	0.90	1.41
G	0.05	0.20
H	0.15	0.31

■ Suggested pad layout



DO-214AA(SMB)	
Dim	Millimeters
P1	6.8
P2	4.3
P3	1.8
Q1	2.5
Q2	2.3



SMBJ TSS SERIES

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.