





Surface Mount High Efficient Rectifier



Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- Fast switching for high efficiency
- High forward surge capability
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Part no. with suffix "Q" means AEC-Q101 qualified

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, automotive and telecommunication.

Mechanical Data

- **Package:** DO-214AA (SMB)
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	HS3ABQ	HS3BBQ	HS3DBQ	HS3FBQ	HS3GBQ
Device marking code			HS3AB	HS3BB	HS3DB	HS3FB	HS3GB
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	V	50	100	200	300	400
Maximum RMS Voltage	V _{RMS}	V	35	70	140	210	280
Maximum DC blocking Voltage	V _{DC}	V	50	100	200	300	400
Average rectified output current @60Hz sine wave, resistance load, TL (Fig.1)	I _O	A			3.0		
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, T _j =25°C	I _{FSM}	A			100		
Storage temperature	T _{stg}	°C			-55 ~ +150		
Junction temperature	T _j	°C			-55 ~ +150		

■ Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	HS3ABQ	HS3BBQ	HS3DBQ	HS3FBQ	HS3GBQ
Maximum instantaneous forward voltage	V _F	V	I _{FM} =3.0A		1.0		1.3	
Maximum reverse recovery time	t _r	ns	I _F =0.5A, I _R =1.0A, I _r =0.25A			50		



HS3ABQ THRU HS3GBQ

Maximum DC reverse current at rated DC blocking voltage	I_R	μA	$T_J=25^\circ C$	5	
			$T_J=125^\circ C$	100	
Typical junction capacitance	C_J	pF	$V_R=4V, f=1\text{ MHz}$	60	40

■ Thermal Characteristics ($T_a=25^\circ C$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	HS3ABQ	HS3BBQ	HS3DBQ	HS3FBQ	HS3GBQ
Typical Thermal resistance	$R_{\theta J-A}^{(1)}$	$^\circ C/W$	72				
	$R_{\theta J-L}^{(1)}$		20				

Note:

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with $0.3'' \times 0.3''$ (8.0 mm x 8.0 mm) copper pad areas

■ Characteristics (Typical)











FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
HS3ABQ-HS3GBQ	F1	Approximate 0.1003	3000	48000	13" reel


■ Outline Dimensions



DO-214AA(SMB)		
Dim	Min	Max
A	1.85	2.15
B	3.30	3.94
C	4.05	4.75
D	1.99	2.61
E	5.21	5.59
F	0.90	1.41
G	0.05	0.20
H	0.15	0.31




■ Suggested pad layout



DO-214AA(SMB)	
Dim	Millimeters
P1	6.8
P2	4.3
P3	1.8
Q1	2.5
Q2	2.3

■ Marking Information



Note:

1. All marking is at middle of the product body
2. All marking is in laser printing
3. XXXX is marking code, like HS3GBQ marking code is HS3GB.
4. Body color: Black
5. YWW is date code, "Y" is year. "WW" is week.

For instance:

The 17th week of 2024, date code is 417
The 17th week of 2025, date code is 517



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com> , or consult your nearest Yangjie's sales office for further assistance.