


Surface Mount Ultra Fast Recovery Rectifier




Features

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- High forward surge capability
- Super Fast reverse recovery time
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Part no. with suffix "Q" means AEC-Q101 qualified

Typical Applications

For use in high frequency rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, automotive and telecommunication.



Mechanical Data

- **Package:** SOD-123FL
Molding compound meets UL 94 V-0 flammability rating, RoHS-compliant, halogen-free
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	U1AQ	U1BQ	U1CQ	U1DQ
Device marking code			U1A	U1B	U1C	U1D
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	V	50	100	150	200
Maximum RMS Voltage	V _{RMS}	V	35	70	105	140
Maximum DC blocking Voltage	V _{DC}	V	50	100	150	200
Average rectified output current @60Hz sine wave, Resistance load, T _L (Fig.1)	I _O	A	1.0			
Forward Surge Current (Non-repetitive) @60Hz Half-sine wave, 1 cycle, T _J =25°C	I _{FSM}	A	40			
Current squared time @1ms≤t≤8.3ms T _J =25°C	I ² t	A ² s	3.735			
Storage temperature	T _{stg}	°C	-55 ~ +175			
Junction temperature	T _J	°C	-55 ~ +175			



■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS	U1AQ	U1BQ	U1CQ	U1DQ
Maximum instantaneous forward voltage	V_F	V	$I_F=1.0A$	0.92			
Maximum reverse recovery time	T_{RR}	ns	$I_F=0.5A, I_R=1.0A, I_{rr}=0.25A$	25			
Maximum DC reverse current at rated DC blocking voltage per diode@ $V_{RM}=V_{RRM}$	I_R	μA	$T_J=25^\circ C$	2			
			$T_J=125^\circ C$	20			
Typical junction capacitance	C_J	pF	$V_R=4V, f=1MHz$	15			

■Dynamic Characteristics

PARAMETER	SYMBOL	UNIT	TEST CONDITIONS		U1AQ	U1BQ	U1CQ	U1DQ
Typical reverse Recovery Time	T_{RR}	ns	$T_J=25^\circ C$	$I_F=1A, di/dt=-50A/us$ $V_{RM}=30V$	25			
			$T_J=25^\circ C$	$I_F=1A$ $di/dt=-200A/us$ $V_{RM}=100V$	18			
			$T_J=125^\circ C$		24			
Typical peak recovery current	I_{RRM}	A	$T_J=25^\circ C$		2.4			
			$T_J=125^\circ C$		4			
Typical reverse recovery charge	Q_{rr}	nC	$T_J=25^\circ C$		20			
			$T_J=125^\circ C$		45			

■Thermal Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	U1AQ	U1BQ	U1CQ	U1DQ
Typical Thermal resistance	$R_{\theta J-A}^{(1)}$	$^\circ C/W$	65			
	$R_{\theta J-L}^{(1)}$		25			
	$R_{\theta J-C}^{(1)}$		20			

Note:

(1) Thermal resistance between junction and ambient and between junction and lead mounted on P.C.B with 3mm*3mm copper pad areas.



■ Characteristics (Typical)

Fig.1:Forward Current Derating Curve




Fig.2:Maximum Non-Repetitive Peak Forward Surge Current




Fig.3:Typical Instantaneous Forward Characteristics




Fig.4:Typical Reverse Leakage Characteristics






FIG.5: Diagram of circuit and Testing wave form of reverse recovery time



■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
U1AQ- U1DQ	F1	Approximate 0.0169	3000	30000	120000	7" reel

■ Marking Information




Note:

1. All marking is at middle of the product body
2. All marking is in laser printing
3. XXXXX is marking code, like U1DQ marking code is U1D
4. Body color: Black
5. YWW is date code, "Y" is year. "WW" is week.

For instance:


The 17th week of 2021, date code is 117
The 17th week of 2022, date code is 217

■ Outline Dimensions



SOD-123FL		
Dim	Min	Max
A	1.60	1.90
B	0.90	1.10
C	2.55	2.85
D	3.60	3.90
E	1.00	1.20
F	0.40	0.90
G	0.10	0.25
H	-	0.05

■ Suggested pad layout



SOD-123FL	
Dim	Millimeters
P1	3.90
P2	1.90
Q1	1.00
Q2	1.50



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, lifesaving, lifesustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.